


## SAE O-Ring boss/SAE O-Ring boss


### Male SAE O-Ring boss/male SAE O-Ring boss



#### Part no. 2229-(Dash size)

Dash size	Tube O.D.		Threads T1	Thread T2	A		B		①
	mm	in			mm	in	mm	in	
8-8S	12,7	0.50	3/4-16	3/4-16	30,3	1.19	11,2	0.44	22,3 0.88
16-16S	25,4	1.00	1 5/16-12	1 5/16-12	43,9	1.73	15,0	0.59	38,1 1.50


### 90° female SAE O-Ring boss/adjustable SAE O-Ring boss male



#### Part no. FF2591-(Dash size)

Dash size	Tube O.D.		Threads T1	Thread T2	A		B	
	mm	in			mm	in	mm	in
0404S	6,4	0.25	7/16-20	7/16-20	21,6	0.85	32,0	1.26
0606S	9,5	0.38	9/16-18	9/16-18	23,9	0.94	37,8	1.49

### SAE O-Ring boss (adj.)/hose connector



#### Part no. FF1167-(Dash size)

Dash size	Tube O.D.		Threads T1	A		B		C	
	mm	in		mm	in	mm	in	mm	in
0808S	12,7	0.5	3/4-16	39,0	1.54	40,4	1.60	12,7	0.50
1010S	16,0	0.63	7/8-14	43,4	1.70	52,3	2.06	16,0	0.63
1212S	19,0	0.75	1 1/16-12	49,8	1.96	52,3	2.06	19,0	0.75
2020S	31,7	1.25	1 5/8-12	55,9	2.20	60,5	2.38	31,7	1.25

**Note:** Available without O-Ring. Order by Part no. FF1161- (Dash size).  
Clamp required.