


Adapters and tube fittings

ORS to SAE 37° (JIC) flare

J

ORS to SAE 37° flare


ORS female swivel/SAE 37° male flare



Part no. FF2209T-(Dash size)

Dash size	Tube O. D.		Thread T1	Thread T2	A		B	
	mm	in			mm	in	mm	in
0412S	6,4	0.25	9/16-18	1 1/16-12	50,5	1.99	21,8	0.86
0612S	9,7	0.38	11/16-16	1 1/16-12	52,6	2.07	21,8	0.86
0808S	12,7	0.50	13/16-16	3/4-16	51,6	2.03	16,8	0.66
0812S	12,7	0.50	13/16-16	1 1/16-12	57,2	2.25	21,8	0.86
1212S	19,0	0.75	1 3/16-12	1 1/16-12	62,0	2.44	21,8	0.86
1616S	25,4	1.00	1 7/16-12	1 5/16-12	71,6	2.82	23,1	0.91
2016S	31,8	1.25	1 11/16-12	1 5/16-12	73,1	2.88	23,1	0.91

Male ORS/SAE 37° male flare




Part no. FF2313T-(Dash size)

Dash size	Tube O. D.		Thread T1	Thread T2	A		B		①
	mm	in			mm	in	mm	in	
0808S	12,7	0.50	13/16-16	3/4-16	39,1	1.54	16,8	0.66	22,3 0.88
1010S	16,0	0.63	1-14	7/8-14	46,5	1.83	19,3	0.76	26,9 1.06
1212S	19,0	0.75	1 3/16-12	1 1/16-12	52,1	2.05	21,8	0.86	31,8 1.25

ORS/ORS

ORS/ORS adapter



Part no. FF2000T-(Dash size) (Ref. SAE 520101)

Dash size	Tube O. D.		Thread T1	Thread T2	A		①
	mm	in			mm	in	
0404S	6,4	0.25	9/16-18	9/16-18	27,4	1.08	15,7 0.62
0604S	9,7	0.38	11/16-16	9/16-18	29,7	1.17	19,0 0.75
0606S	9,7	0.38	11/16-16	11/16-16	31,0	1.22	19,0 0.75
0806S	12,7	0.50	13/16-16	11/16-16	33,8	1.33	22,3 0.88
0808S	12,7	0.50	13/16-16	13/16-16	35,3	1.39	22,3 0.88
1008S	16,0	0.63	1-14	13/16-16	39,9	1.57	26,9 1.06
1010S	16,0	0.63	1-14	1-14	42,7	1.68	26,9 1.06
1208S	19,0	0.75	1 3/16-12	13/16-16	42,9	1.69	31,8 1.25
1210S	19,0	0.75	1 3/16-12	1-14	45,7	1.80	31,8 1.25
1212S	19,0	0.75	1 3/16-12	1 3/16-12	47,2	1.86	31,8 1.25
1612S	25,4	1.00	1 7/16-12	1 3/16-12	48,8	1.92	38,1 1.50
1616S	25,4	1.00	1 7/16-12	1 7/16-12	49,3	1.94	38,1 1.50
2020S	31,8	1.25	1 11/16-12	1 11/16-12	51,3	2.02	44,4 1.75
2424S	38,1	1.50	2-12	2-12	53,1	2.09	53,9 2.12